



.300 Head Drive Pins

STANDARD PINS

Drive pins with a 0.300" diameter head are designed for permanently fastening a fixture to concrete, some types of masonry and A36 structural steel. Drive pins are manufactured with a 0.145" diameter shank in various lengths. Knurled shank designs are available to increase performance in steel base materials. A plastic flute is mounted over the point to retain the drive pin in the fastener guide of the tool providing guidance during the driving operation.

.300 HEAD DRIVE PINS

| CAT. NO. | SHANK LENGTH | HEAD DIA. | SHANK DIA. | STD. BOX | STD. CTN. |
|----------|----------------|-----------|------------|----------|-----------|
| 50012 | 1/2" (knurled) | .300 | .145 | 100 | 5000 |
| 50016 | 5/8" (knurled) | .300 | .145 | 100 | 5000 |
| 50022 | 3/4" | .300 | .145 | 100 | 5000 |
| 50023 | 3/4" Black | .300 | .145 | 100 | 5000 |
| 50026 | 1" | .300 | .145 | 100 | 5000 |
| 50030* | 1-1/8" | .300 | .145 | 100 | 1000 |
| 50032 | 1-1/4" | .300 | .145 | 100 | 1000 |
| 50034 | 1-1/2" | .300 | .145 | 100 | 1000 |
| 50038 | 2" | .300 | .145 | 100 | 1000 |
| 50040 | 2-1/4" | .300 | .145 | 100 | 1000 |
| 50042* | 2-3/8" | .300 | .145 | 100 | 1000 |
| 50044 | 2-1/2" | .300 | .145 | 100 | 1000 |
| 50046 | 2-3/4" | .300 | .145 | 100 | 1000 |
| 50048 | 3" | .300 | .145 | 100 | 1000 |

* Discontinued item once current stock exhausted.

MASTER PACK

| CAT. NO. | SHANK LENGTH | HEAD DIA. | SHANK DIA. | STD. BOX | STD. CTN. |
|----------|------------------|-----------|------------|----------|-----------|
| 50980 | 1/2" knurled | .300 | .145 | 1000 | 5000 |
| 51041 | 3/4" Black Pins | .300 | .145 | 1000 | 5000 |
| 53300 | 5/8" knurled | .300 | .145 | 1000 | 5000 |
| 53400* | 5/8" knr.Top Hat | .300 | .145 | 1000 | 5000 |
| 51040 | 3/4" | .300 | .145 | 1000 | 5000 |
| 51100 | 1" | .300 | .145 | 1000 | 5000 |
| 51160 | 1-1/4" | .300 | .145 | 1000 | 5000 |
| 51340 | 1/2" knr.Top Hat | .300 | .145 | 1000 | 5000 |
| 51400 | 3/4" Top Hat | .300 | .145 | 1000 | 5000 |
| 51520 | 1" Top Hat | .300 | .145 | 1000 | 5000 |

* Discontinued item once current stock exhausted.



.300 HEAD STEP SHANK PINS

| CAT. NO. | SHANK LENGTH | HEAD DIA. | SHANK DIA. | STD. BOX | STD. CTN. |
|----------|-----------------|-----------|------------|----------|-----------|
| 50158* | 3/4" Step Shank | .300 | .145/.130 | 100 | 5000 |
| 50159* | 1" Step Shank | .300 | .145/.130 | 100 | 5000 |

* Discontinued item once current stock exhausted.



.300 HEAD BLUE MAGIC™ DRIVE PINS

Blue Magic™ pins offer a hard plastic flute for improved centering in the tool and tip protection.

| CAT. NO. | SHANK LENGTH | WT./ 100 | SHANK DIA. | STD. BOX | STD. CTN. |
|----------|--------------|----------|------------|----------|-----------|
| 56000 | 1/2" | .900 | .145 | 100 | 5000 |
| 56004 | 3/4" | .900 | .145 | 100 | 5000 |
| 56006 | 1" | .900 | .145 | 100 | 5000 |
| 56012 | 1-1/2" | .900 | .145 | 100 | 5000 |



.300 HEAD DRIVE PINS WITH TOP HAT

The pins listed below are used primarily for applications fastening drywall track to concrete or steel. They are assembled with a metal top hat to provide extra bearing surface against the drywall track.

| CAT. NO. | SHANK LENGTH | HEAD DIA. | SHANK DIA. | STD. BOX | STD. CTN. |
|----------|--------------|-----------|------------|----------|-----------|
| 50136 | 1/2" knurled | .300 | .145 | 100 | 5000 |
| 50138 | 5/8" knurled | .300 | .145 | 100 | 5000 |
| 50140 | 3/4" | .300 | .145 | 100 | 5000 |
| 50144 | 1" | .300 | .145 | 100 | 5000 |



WASHERED PINS

To provide resistance to pullover, these pins are available with preassembled 14 gage (0.075") metal washers in various diameters. The insulation washer has a thickness of 0.035".

.300 HEAD DRIVE PINS WITH 3/4" WASHER

| CAT. NO. | SHANK LENGTH | HEAD DIA. | SHANK DIA. | STD. BOX | STD. CTN. |
|----------|--------------|-----------|------------|----------|-----------|
| 50070 | 3/4" | .300 | .145 | 100 | 1000 |
| 50080 | 2-1/2" | .300 | .145 | 100 | 1000 |

.300 HEAD DRIVE PINS WITH 7/8" WASHER

| CAT. NO. | SHANK LENGTH | HEAD DIA. | SHANK DIA. | STD. BOX | STD. CTN. |
|----------|--------------|-----------|------------|----------|-----------|
| 50090 | 1" | .300 | .145 | 100 | 1000 |
| 50092 | 1-1/4" | .300 | .145 | 100 | 1000 |
| 50094 | 1-1/2" | .300 | .145 | 100 | 1000 |
| 50096 | 2" | .300 | .145 | 100 | 1000 |
| 50098 | 2-1/2" | .300 | .145 | 100 | 1000 |
| 50100 | 3" | .300 | .145 | 100 | 1000 |

.300 HEAD DRIVE PINS WITH 1" WASHER

| CAT. NO. | SHANK LENGTH | HEAD DIA. | SHANK DIA. | STD. BOX | STD. CTN. |
|----------|--------------|-----------|------------|----------|-----------|
| 50108 | 1-1/4" | .300 | .145 | 100 | 1000 |
| 50110 | 1-1/2" | .300 | .145 | 100 | 1000 |
| 50112 | 2" | .300 | .145 | 100 | 1000 |
| 50114 | 2-1/2" | .300 | .145 | 100 | 1000 |
| 50116 | 3" | .300 | .145 | 100 | 1000 |