

## Chalk



2032160

64901

- High visibility chalk for self chalking line reels
- For use on a variety of surfaces including wood, drywall, concrete, stone, and metal
- Permanent colors, especially black and red, produce long lasting lines that won't fade
- Temporary colors, especially white and blue, provide high visibility and are easy to remove
- Proprietary formulations for dark, sharp lines and reliable performance
- Chalk containers are filled by weight, not volume

## Chalk Reels



64311

- Durable Aluminum Alloy Construction
- Steel plated hook designed for stable anchoring
- Retractable locking handle allows reel to be used as a plumb bob
- Leak-proof side fill opening
- Twisted line holds more chalk for multiple re-strikes

## Crayons



66402

- For use on oily, slick, wet, cold or dry surfaces
- Ideal for lumber, concrete, ceramics and metal
- Non-toxic, waterproof

## China Markers



02089-SH

- Ideal for writing on china, glass, metal or plastic
- Marks on porous and non-porous surfaces
- Fade and moisture resistant
- Write length of 2500 ft.

## Carpenter Pencils



66300

- 7" overall length
- Uses 50% less pencil per sharpening cycle

## Carpenter Pencil Sharpener



233250


- Integrated emery board for fine point filing
- Narrow sharpening angle for broader, more durable point reduces lead breaking

## Tapes



- Weatherproof poly vinyl chloride for harsh outdoor conditions
- Ideal for construction, landscaping, excavating, identification of trees or hazards, and locating underground cables or pipe
- 1-3/16" wide
- Bright, fade-resistant color for maximum visibility
- Constructed of non-adhesive, non-conductive vinyl
- 3" wide, 3 mm thick

## Flags



- Dimensions: 2-1/2" x 3-1/2" x 21"
- Packaged in bundles of 100
- Bright colors for maximum visibility
- Durable compounds resist fading

# KESON<sup>®</sup>



## The Original Keson by Swanson Speed Square

This time-tested tool is a framing, tri-mitre square, saw guide, plus a protractor square in one compact tool! Common rafter & hip valley rafter scales permits a 1 number reference for all cuts. Only 7" x 7" x 10", this ingenious square is made from 3/16" aluminum alloy for extra durability. Packaged 24 per carton with the "Blue Book" for Roof & Stairway Layout guide on attractive hang cards & cut case carton.

## K-Line Nylon Coated Steel Tape Measure

The Keson K-Line makes measuring easy. The dual-sided two color blade lets you measure in feet/inches/eighths or in feet/tenths. K-line measuring tapes are accurate, resilient, durable and dependable.



- Superior accuracy, easy-to-read graduations
- Maximum durability
- 2 Sided printing
- 2 Color blade
- Ideal for all home projects

Description	Graduations	Length
Dual side nylon coated steel	Feet and Inches	100 ft.
Dual side nylon coated steel	Feet and Inches	200 ft.

## STRIPE INVERTED TIP WATERBASE MARKER

### General Description:

A fast drying marking paint applied in an inverted position that is lead free and V.O.C. compliant.

### Suggested Uses:

- Utility marking; buried water, gas, electric and telephone lines
- Golf courses
- Landscaping
- Construction sites
- Athletic fields
- Surveyor's marking
- Excavation sites
- Mining

### Benefits:

- Non-clogging
- Safe on grass
- Fast dry
- Produces vivid lines
- Meets APWA standard colors
- Lead free
- V.O.C. Compliant
- Converta-Cap allows spraying without removing and prevents accidental use

### Additional Information:

May be actuated by hand or may be used with the #Z-606 Marking Wand or #Z-605 Marking Gun. While it has a water base formulation, it will not wash away.



### Color:

- High-Visibility Yellow
- Red
- White
- Orange Fluorescent
- Green Fluorescent
- Blue Fluorescent
- Hot Pink Fluorescent

## MRO COLD GALV PRIMER

### General Description:

A smooth cold galvanizing compound that dries to a durable, crack resistant coating to protect iron and steel surfaces.

### Suggested Uses:

Effective touch-up for all marred or scratched hot dip galvanized surfaces:

- Vehicle bodies
- Bridges
- Railroad equipment
- Trailers
- Storage tanks
- Marine equipment
- Piping
- Agricultural equipment

### Benefits:

- Fast dry
- Abrasion resistant
- May be painted over
- Excellent outdoor durability
- Lead free, chromate free
- Sag-free spray
- Stops rust creepage
- Resists chemicals
- Tough, permanent hard coat

### Additional Information:

Electrochemical galvanic action continues to protect even if scratched.

Meets or exceeds the following performance requirements of MIL Specs: MIL-P-26915B, MIL-P-46105, DOD-P-21035A

Dried paint film contains a minimum of 90% zinc.

Part # 620-1445 (Cold Galv. Primer)

### Also Available:

- Clear #20631
- RedIron Oxide Primer #16-807



## GREEN EPOXY REBAR COATING

#16-547

Specially formulated green epoxy primer that is designed especially for touch-up of rebar to help extend its life cycle. Meets ASTM A775, D3963, and D3963M-01 performance requirements regarding the repair of defects in organic coatings for rebar. Also, passes ASTM B117 (Salt fog) and ASTM G20 (chloride permeability). Recommended film thickness: 0.5-1.0 mil. dry film.

### Suggested Uses:

Rebar touch up of cut ends to use on reinforced concrete. Ideal for spot repair of damaged coatings.

### Benefits:

Overspray is reduced  
Exceptional protection against rust and corrosion  
Resists corrosion from seacoast exposure

### Packaging:

UPC Code	043281000451
Cans per case	12
Shipping weight per case	15 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	ORM-D, UN 1950
Hazard Class	2.1