

Drive Pins



ITW Ramset/Red Head powder actuated fasteners are specifically fabricated to meet the exacting requirements of toughness and durability that enable them to penetrate dense concrete and structural quality steel.

Selection Charts

BLACK TRACK PINS *Designed for use in concrete and structural steel applications*

AVAILABLE IN 100-PACK OR 1000-PACK PER BOX.



PART NUMBER	SHANK LENGTH		721	AUTO FAST	D60	SA270	D45A	COBRA	RS22/HD22
	IN.	(MM)							
1503KBC	1/2 Knurled	(12.7)	■	■	■	■	■	■	■
1506BC	3/4	(19.1)	■	■	■	■	■	■	■
1508BC	1	(25.4)	■	■	■	■	■	■	■

Shank diameter = .145
Head diameter = .300

DRIVE PINS *Designed for use in concrete and structural steel applications*

100 PER BOX.



PART NUMBER	SHANK LENGTH		721	AUTO FAST	D60	SA270	D45A	COBRA	RS22/HD22
	IN.	(MM)							
1503K*	1/2 Knurled	(12.7)	■	■	■	■	■	■	■
1506*	3/4	(19.1)	■	■	■	■	■	■	■
1508*	1	(25.4)	■	■	■	■	■	■	■
1510*	1-1/4	(31.8)	■	■	■	■	■	■	■
1512	1-1/2	(38.1)	■	■	■	■	■	■	■
1513	1-3/4	(44.5)	■	■	■	■	■	■	■
1514	2	(50.8)	■	■	■	■	■	■	■
1515	2-3/8	(60.3)	■	■	■	■	■	■	■
1516	2-1/2	(63.5)	■	■	■	■	■	■	■
1524	3	(76.2)	■	■	■	■	■	■	■

*Also available in 1000 Pack
Shank diameter = .145
Head diameter = .300

POWERPOINT PINS *Used for fastening into harder steel and concrete. Premium steel and hard concrete pin*

100 PER BOX.



PART NUMBER	SHANK LENGTH		721	AUTO FAST	D60	SA270	D45A	COBRA	RS22/HD22
	IN.	(MM)							
SP12	1/2	(12.7)	■	■	■	■	■	■	■
SP58	5/8	(15.9)	■	■	■	■	■	■	■
SP34	3/4	(19.1)	■	■	■	■	■	■	■
SP78	7/8	(22.2)	■	■	■	■	■	■	■

Shank diameter = .150
Head diameter = .300