

Cutting Wheels

OLYMPIA



Double Reinforced Wheels

Available in
4 1/2", 7", 12",
14" Specify
1" or 20mm
Arbor

- Double reinforced
- Strong resin bond
- High quality grain
- Cuts square and resists breakage
- Long life and burr free cutting
- Fast cut rate

Metal

Aluminum Oxide
grain
Red color code

Primary

Application:

Metal, tubing, structural steel,
bars, pipe, angle iron, rebar



Masonry

Silicon Carbide
grain
Green color code

Primary

Application:

Concrete, brick, masonry,
block, ceramic, asphalt



- Ideal for low horsepower chop saws
- 3/32" blade thickness
- Minimum burr
- Double reinforced
- Fast cutting and long life
- 12" & 14" available

Depressed Center Grinding Wheels

- Type 27 & Type 28 configurations
- Internally reinforced with high strength fiberglass layers
- Most popular raised hub wheel
- Use on right angle grinder
- Safety combined with controlled performance
- Designed for both grinding & bending applications
- Available in 4 1/2", 7" and 9"
- 5/8 -11" Arbor



Metal A24S

- Unique dual grit construction for rough & finish grinding with one wheel
- Pipe cutting
- Designed for cut off & grinding
- Red color code

Primary Application:

- Welds, steel, iron, ferrous metals



Masonry C24S

- Silicon Carbide grain
- Designed for high stock removal
- Green color code

Primary Application:

- All concrete and masonry products plus nonferrous metals (aluminum, brass, copper)



Zirconia AZ24T

- High performance wheel
- Alumina Zirconia
- High metal removal with extremely long life
- Blue color code

Primary Application:

- Stainless, cast iron, high temperature alloys and steel



Aluminum A/C 24S

- Aluminum Oxide/Silicon Carbide grain
- Grey color code

Primary Application:

- Nonferrous metals & stainless steel

ATLAS ABRASIVES COMPANY

Flared Cup Wheels

Flared cup wheels are used for fast rough grinding of major blemishes in concrete. Designed for use with standard grinding machines they come with a built-in 5/8" diameter threaded mount. Flared cup wheels are available in 4" or 6" diameter.



Rubbing Blocks, 3 x 6 and 3-1/2 x 8

Fluted concrete rubbing blocks are a low-cost, fast cutting hand tool for removing concrete form and mold marks. They are also recommended for dressing all types of concrete surfaces. The flutes provide better shearing action and reduce cement dust loading. These blocks are available from MCS with or without handle, in two popular sizes.

