



Haz Mat Storage



Type I Safety Cans

Eagle Type I Safety Cans

Eagle galvanized Type I cans meet OSHA and NFPA Code 30 requirements and are FM, UL and ULC Approved for safe handling and storage of gasoline and other flammable liquids. These Type I cans feature deep drawn, 2-piece, no-weld construction with no top or side seams, non-sparking brass pour spout and flame arrestor and a spring-closing lid with neoprene gasket that safely relieves internal pressure at 5 psi. The cans are finished with a bright red powder coat with yellow silk-screened label in English,



Spanish and French. These cans are also available in blue for kerosene and yellow for diesel and include specific labeling. The optional F-15 HDPE funnel fits the 1, 2 and 5 gallon cans and makes filling and dispensing easier.

Lead Free

Eagle cans feature environmentally friendly

Lead Free Technology, constructed of 24-gauge hot dipped galvanized steel. Other manufacturers' safety cans use lead coated terne steel. Compliance: OSHA 29 CFR 1910.106, 1925.152 and NFPA Code 30



Speed Bump-Cable Protector

Slow down the traffic with these extra durable units constructed of high density polyethylene. Versatile design handles the heaviest of vehicle loads while also acting as a dual channel cable protector. Protect air lines, water lines and electric cables from damage. Flexible design fits contour of road or factory floor. High visibility yellow HDPE with non-skid surface resists weather (UV) and chemical damage. Easy installation with included anchor kit.

Dimensions: 10"W x 72"L x 2"H, Wt. 15 lbs.
 Cable channel measures 1.25"W x .875"H.



Speed Bump-Cable Protector

Model	Description	Dimensions	Weight
1792	Speed Bump-Cable Guard	10"Wx72"Lx2"H	15 lbs.



1923 24 Gallon
23" x 18" x 65"

New cabinets for specialized use. We were the first to offer the cabinet selection we do.

Eagle's Newest Specialty Use Cabinets

Specialty Use Cabinets

- 22 gallon under counter
- 24 gallon wall mount
- 24 gallon space saver

Space Saver Storage Cabinets

Only 23" wide, this cabinet features a 24 gallon capacity that will fit places a conventional cabinet can't--this one door cabinet is available in either self closing or manual closing.

Wall Mount Safety Storage Cabinets

Just 12" deep, this cabinet will fit easily on the wall above work spaces and is convenient for eye level storage of flammables and will hold 24 gallons.

Under The Counter Safety Storage Cabinets

Optimize your work area with this compact cabinet. This 22 gallon cabinet is designed with 3" kick space. It fits well under counters, fume hood or under windows.



1976 24 Gallon
43" x 12" x 44"

1970 24 Gallon
35" x 22" x 35"

Meet OSHA and FNPA Code 30 Specifications Self-Closing Models Meet UFC 79

Capacity	W x D x H	Closing Type		#Shelves	Shelf Depth	Max. Weight	
		Sliding Self Closing	Manual Close				
22 gallon	35" x 22" x 35"	-	1971	1970	1	18 3/4"	215 lbs.
24 gallon	43" x 12" x 44"	-	1976	1975	3	8 3/4"	235 lbs.
24 gallon	23" x 18" x 65"	-	1923	2310	3	14 3/4"	270 lbs.



Haz Mat Storage



1620 2 Drum-66 Gallon Spill Capacity
 51" x 26 1/4" x 15"



1640 4 Drum-90 Gallon Spill Capacity
 51 1/2" x 51 1/2" x 18 1/2"

NEW!



1646 4 Drum Nestable-66 Gallon Spill Capacity
 58 1/2" x 58 1/2" x 7 3/4"



1612 Single Drum Containment Unit w/1698 Dolly
 65 Gallon Spill Capacity

Spill Contaminant Pallets

Eagle makes four forkliftable pallets for the containment of hazardous spills. These models include the 1620 2-drum pallet with a 66 gallon spill capacity, the 1640 4-drum pallet with a 90 gallon secondary spill capacity, the 1645 low profile 4-drum pallet with a 66 gallon secondary spill capacity and the 1646 Nestable 4-drum pallet with a 66 gallon secondary spill capacity. All pallets feature:

- Polyethylene construction for excellent chemical resistance
- Grating with 1 3/4" square opening that removes easily for cleaning
- Forkliftable design with 3/4" drain plug
- Model 1645 and 1646 are compatible with our Model 1689 ramp
- Meet EPA requirements for secondary spill containment of hazardous materials (40 CFR 264.175)

The 1612 is a single drum containment unit that is ideal for use as a spill containment unit, a mobile pumping station or waste collection station. With the addition of the 1698 drum dolly you can easily move the drum for dispensing or collection.

Model	Item	Dimensions	Weight	Load Capacity
1612	Single Drum Unit	31" x 33"	30 lbs.	-
1620	2 Drum Pallet Unit	51" x 26 3/4" x 15"	48 lbs.	2,000 lbs.
1640	4 Drum Pallet Unit	51 1/2" x 51 1/2" x 18 1/2"	88 lbs.	4,000 lbs.
1645	4 Drum Pallet Unit-Low Profile	51 1/2" x 51 1/2" x 10"	65 lbs.	8,000 lbs.
1646	4 Drum Nestable Pallet	58 1/2" x 58 1/2" x 7 3/4"	65 lbs.	6,000 lbs.
1689	Poly Ramp for 1645 & 1646	45 1/2" x 32" x 8"	32 lbs.	1,500 lbs.
1689BLK	Black Poly Ramp for 1645 & 1646	45 1/2" x 32" x 8"	32 lbs.	1,500 lbs.
1698	Single Drum Containment Dolly	26 1/2" x 7"	25 lbs.	1,000 lbs.

MADE IN



1645 4 Drum - 66 Gallon Spill Capacity
 51-1/2" x 51-1/2" x 10"