





Global Sealer
Technologies

High Gloss Wet Look Lacquer



*Clear Sealer for
Decorative Concrete
& Masonry Surfaces*



Our solvent-based, high gloss, crystal clear, deep penetrating sealer is designed for decorative concrete, paving stone and natural stone surfaces, to enhance and beautify their natural color.

- Easily applied, fast drying, long lasting
- Interior and exterior use
- Inhibits efflorescence
- Gas, oil and grease resistant
- Water repellent
- Non-yellowing and UV resistant

www.gstinternational.com



High Gloss Wet Look Lacquer

Clear Sealer for Decorative Concrete & Masonry Surfaces

Overview

DESCRIPTION:

GST International's High Gloss Wet Look Lacquer is a solvent based, high gloss, crystal clear, deep penetrating barrier coating for decorative concrete, stone, natural and manufactured hardscape surfaces. **High Gloss Wet Look Lacquer** provides a "water-wet" appearance which enhances and beautifies the natural color of the applied masonry surface. Non yellowing **High Gloss Wet Look Lacquer** seals against food stains, gasoline, grease, oils, water and acid. Its deep bonding formula resists peeling, chipping, cracking and UV degradation. Made from the latest developments in VOC compliant high solids acrylic chemistry, **High Gloss Wet Look Lacquer** delivers excellent resistance to the formation of efflorescence. When used on newly placed concrete, the sealer can help protect against spalling, dusting, freeze-thaw damage and alkali degradation. **High Gloss Wet Look Lacquer** remains hard even under extreme sunlight and delivers superior wear resistance. Its VOC compliant formula works great indoors and outdoors to provide a breathable barrier that allows moisture to escape from the coated surfaces. Also, it is effective as a joint sand stabilizer for interlocking pavers.

LIMITATIONS:

Not recommended for pre-sealed surfaces or non-porous surfaces such as ceramic tile, marble, granite, porcelain and terrazzo. Do not use where hydrostatic pressure is possible.

USE ON:

- Standard concrete
- Colored and stamped concrete
- Exposed aggregate concrete
- Natural stone • Slate
- Manufactured stone
- Interlocking pavers
- Porous brick • Mexican tile

FEATURES:

- Use indoors or outdoors
- Non-yellowing, UV resistant
- Fast drying and long lasting
- Easy to apply by brush or spray
- Retards efflorescence
- Resistant to oil and grease stains
- Excellent adhesion
- Water repellent
- Re-coatable

Specifications:

VOC: 262 g/l
FLASH POINT: -4 °F - 20 °C
WEIGHT PER GALLON: 7.1 lbs./gal
APPEARANCE: Clear
ODOR: Medium
PACKAGE VISCOSITY: 19 sec. Zahn Cup #2
SOLIDS by VOLUME: 20%

COVERAGE:

Porous Surface 50 – 200 sq.ft./gal
Dense Concrete 200 – 400 sq.ft./gal

For exact coverage rates, a measured quantity to proper saturation over a known area will provide a square foot coverage rate for a specific job.

DRY SCHEDULE:

Dry Time: 10 to 30 mins
Cure Time: 24 to 48 hrs
Rainproof: 24 hrs

PRODUCT CODE: 1A-501HG

SHIPPING DESCRIPTION: Ground/Air/Vessel

Name: Paint, 3, UN1263, PG II

Required Label: FLAMMABLE LIQUID

Required Marking: PAINT UN1263

UNIFORM FIRE CODE: CLASS I-B

STORAGE TEMPERATURE: 120° F. max.

SHELF LIFE: Unlimited

HMIS RATINGS: H - 2; F - 3; R - 0; PP - H

CLEAN UP: Lacquer thinner or xylene

REMOVE: Chemical stripper

PACKAGING: Available in gallons and 5 gallon pails

All products are available in standard one gallon and five gallon sizes. 55 gallon drums and 275 gallon totes are also available upon request.

MANUFACTURED IN THE USA



High Gloss Wet Look Lacquer

Clear Sealer for Decorative Concrete & Masonry Surfaces

IMPORTANT NOTE:

Before use on a job, thoroughly test this product on a sample to assure performance and appearance. Use only in well ventilated areas. Immediately remove pools or puddles where over application has occurred.

SURFACE PREPARATION:

Surface must be completely clean and dry to the touch. Remove all dirt, wax, old paints or sealers with appropriate cleaner or chemical stripper. If muriatic acid has been used the surface must be flushed with clean water and neutralized with a pH neutralizer. We do not recommend muriatic acid for cleaning concrete as it will discolor the surface, etch the concrete and is hazardous to use. After cleaning, allow surface to dry 24 hours prior to sealer application. Allow new concrete to cure for at least 28 days before applying sealer.

THINNING: Not required - use as is

APPLICATION:

High Gloss Wet Look Lacquer can be applied with a brush, roller, or most types of airless spray equipment. One coat will seal, protect and enhance the beauty of the surface. If a second coat is necessary due to extreme porosity, apply as soon as the first coat is dry to the touch. For most applications, a pump-up garden sprayer with solvent resistant seals is convenient, however, do not allow the lacquer to dry on the spray tip. If this occurs, soak tip in lacquer thinner and clean with a stiff brush.

Do not apply **High Gloss Wet Look Lacquer** during inclement weather or in direct sunlight when temperature exceeds 80°F. Application to a damp surface or incompletely cured concrete may cause a hazy appearance or loss of adhesion. Air and surface temperature should be between 50° and 80°F for 24 hours following application.

Brushsynthetic bristle brush
Roller3/8" nap roller
Low pressure pump sprayer solvent resistant seals
Airless sprayer tip size0.013"- 0.015"

Porous Surfaces - paver brick, flagstone, Mexican clay tile, etc. Generally, one coat will provide complete protection. If a second coat is necessary due to extreme porosity, apply as soon as the first coat is dry to the touch. To strengthen old, porous and crumbling surfaces additional applications may be required.

Dense Surfaces - concrete, slate, limestone, stone, concrete tile, etc. One light to moderate coat supplies complete protection and a high gloss finish. More than one coat for dense surfaces is not recommended.

WATER PENETRATION TEST:

Drop a small amount of water on the sealed surface. If water penetration occurs or if water does not bead up on the surface, the application of additional sealer is required.

CLEANUP: Lacquer thinner or xylene

SAFETY PRECAUTIONS:

WARNING: FLAMMABLE LIQUID AND VAPOR. MAY BE HARMFUL IF SWALLOWED OR INHALED. VAPOR MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA AND CAN CAUSE NOSE AND THROAT IRRITATION. LIQUID CONTACT WITH EYE AND SKIN CAUSES IRRITATION. Contains: 2-propanone, CAS #67-64-1; xylene, CAS #1330-20-7; petroleum hydrocarbon, CAS #64742-94-5; 2-butoxyethanol, CAS #111-76-2; ester mixture; ethylbenzene, CAS #100-41-4; and naphthalene, CAS #91-20-3. Keep away from sparks, heat or open flames. Use with adequate ventilation. Avoid breathing of vapor. Avoid contact with eyes, skin and clothing. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor levels are below applicable limits. Follow respirator manufacturer's directions for use. Keep container closed when not in use. If spillage has occurred, absorb and dispose of according to local regulations.

NOTICE:

Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

**KEEP THIS PRODUCT OUT OF THE
REACH OF CHILDREN**

FIRST AID:

EYES: In case of contact, immediately flush eyes with plenty of water for 15 minutes. Contact a physician if irritation persists or later develops. **SKIN:** In case of contact, wash with soap and water. Remove contaminated clothing and shoes. Do not reuse until cleaned. Contact a physician if irritation persists or later develops. **INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. **INGESTION:** If swallowed get medical attention immediately. DO NOT induce vomiting.

FOR PROFESSIONAL USE ONLY

PRODUCT WARRANTY: The statements made herein, on labels, product bulletins, or by any of GST International employees or agents concerning this product are given for general information only. Due to variables beyond GST International's control in application, surface preparation, surface temperature, humidity and other variable factors GST International assumes no liability for any claim that may arise out of the use of its products and disclaims any warranty expressed or implied relating to the storage, application, thinning, merchantability, Buyer's assumption of performance, and the fitness for a particular purpose. Receipt of products from GST International or its agents constitutes acceptance of the terms of this warranty. In the event that GST International finds that the product delivered is not of GST International's standard quality, GST International will at its sole discretion, either replace the product or refund the purchase price. GST International's choice of one of these remedies shall be the Buyer's sole remedy. GST International will under no circumstances be liable for consequential damages, except insofar as liability is mandated by law. GST International will deliver products at agreed times insofar as it is reasonably able to do so, but it will not be liable for failure to deliver on time when the failure is beyond its reasonable control.



Global Sealer
Technologies

Family of Products:

For Newly Poured Concrete

Use **ConCure** immediately after new concrete is poured. Allow approximately 28 days for new concrete to cure prior to applying any GST Sealer.

Where Efflorescence, Rust or Cement Scale is Present

Use **Efflorescence Remover** to eliminate the white, chalky deposits.

Use **Clean Concrete** to remove rust, cement staining and efflorescence.

Where Cleaning is Needed or Efflorescence Remover Has Been Used

Use **Pro-Grade Cleaner** to thoroughly clean and prepare the surface prior to applying any of the GST sealers.

Use **ProGrade Cleaner** to neutralize pH where **Efflorescence Remover** or **Clean Concrete** was used.

Choose an Invisible or Appearance Enhancing Sealer

To be applied after the surface is clean and dry.

Choose an Appearance Enhancing Sealer:

- Low Sheen Wet Look Lacquer
- High Gloss Wet Look Lacquer
- Lock 'N Seal
- Satin Seal
- Stone Enhance
- Ultacryl
- Final Coat

Choose an Invisible Sealer:

- Water Block
- Stain Block Elite

Product Characteristics:

Use with:

Product Guide

Product Guide	High Gloss	Low Sheen	Satin	Invisible	Light Enhancement	Heavy Enhancement	Repels Water	Repels Grease and Oil	Resists Stains	Resists Efflorescence	Removes Spalling	Removes Oil, Grime	Removes Rust, Efflorescence	Indoor applications	Outdoor applications	Porous Surfaces	Dense Surfaces	Concrete, Exposed Aggregate	Pavers and Slabs	Concrete Block Walls	Brick Masonry	Natural Stone & Travertine	Manufactured Stone	Synthetic Floors	Tiles
High Gloss Wet Look	✓					✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓		✓	✓				
Low Sheen Wet Look		✓	✓			✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓		✓	✓				
High Gloss Low VOC	✓					✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓		✓	✓				
Low Sheen Low VOC		✓	✓			✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓		✓	✓				
Lock n Seal			✓		✓		✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓				
Satin Seal			✓		✓		✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓	✓			
Ultacryl	✓				✓		✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓				
Final Coat	✓				✓									✓			✓	✓			✓		✓	✓	
Stain Block Elite				✓			✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓	✓			
Stone Enhance						✓	✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓	✓			
Water Block				✓			✓	✓	✓	✓	✓			✓	✓	✓	✓	✓	✓	✓	✓	✓			
Pro-Grade Cleaner											✓			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Efflorescence Remover												✓		✓	✓	✓	✓	✓	✓	✓	✓	✓			
Clean Concrete											✓	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓			

All products are available in standard one gallon and five gallon sizes. 55 gallon drums and 275 gallon totes are also available upon request.