

ARDEX ARDIFIX™

Low Viscosity Rigid Polyurethane Crack & Joint Repair

ARDEX ARDIFIX™ is a repair compound for cracks, control joints, spalls and pop-outs on interior or exterior applications. It is ideally suited to fill cracks and saw-cuts prior to the installation of ARDEX MC™ Moisture Control Systems, Underlayments and Toppings.

Key Features

- Two-part polyurethane
- Extremely low viscosity allows for deep penetration
- Service temperature range of -35°F to 110°F (-37 to 43°C)
- No shrinkage
- 100% solids
- Non-flammable

Installation

- **Package:** 21.2 oz. (627 ml) dual cartridge
- **Coverage:** Varies with depth of fill area
- **Initial set:** 2 minutes
- **Tack free:** 10 minutes
- **Full service:** 45 minutes
- **Grind smooth:** 45 minutes

Performance

- **ASTM D638 Tensile Strength:** Approx. 4150 psi (292 kg/cm²)
- **ASTM D638 Elongation:** 6%
- **ASTM D624 Die C Tear:** 243 pli
- **Shore D Hardness:** 70
- **Viscosity:** 60 cps
- **VOC:** 0 g/L



For easy-to-use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at the iTunes Store or Google play.



Refer to the technical data sheet at www.ardexamericas.com or call 888-512-7339 prior to installation. For free ARDEX product training, click on ARDEX Academy.

AF333 11/15

ENGINEERED CONCRETE
REPAIR SYSTEMS



AMERICAS

+1-724-203-5000
888-512-7339
www.ardexamericas.com